



Northstate

Simply better carpet.

BRAVEHEART PRODUCT BULLETIN

ABN 14010558540

Manufacturer	Northstate Carpet Mills
Country of Manufacture	Australia
Fibre System	Strudon [®] Olefin / Ultrel [™] Nylon
Coloration	Solution Dyed / Space Dyed
Construction	Interlocking Level Loop Pile
Pile Weight	16 oz/sq yd 542.51 g/sq m
Backing System	Dual Latex bonding
Primary Backing	Woven Synthetic
Secondary Backing	AIRTEX green
Carpet Protection	Scoured & Extracted [™] to remove processing oils Anti-microbial present in backing laminate.
Fire Hazard Properties (B.C.A. Spec.C1.10a)	Direct-Stick - Tested to AS/ISO 9239-1 Suitable for ALL building classifications, except <u>non-sprinklered</u> Class 9a (Patient Care) and Class 3 (Accommodation for the Aged). Verify building classifications with your local building authority and/or council. <i>Consult your Northstate representative for specific details.</i>
Static Generation (AS2834)	< 3.0kv
Light Fastness	L6
Change on Wet Cleaning	Gray Scale 5
Approx pattern repeat	Not Applicable
Installation Method	Suitable for direct-stick or cushion installations
Chair Protectors	Mandatory under chairs with castors to preserve appearance retention, and avoid premature wear.
Rating - 5 Year Commercial Limited Warranties - 7 Year Residential Limited Warranties <i>see full warranty text for details</i>	Commercial Medium Duty (including stairs) Residential Heavy Duty (including stairs) Abrasive Wear ZipperLock[®] StainFree Anti-Shock ColourFast

- Installation to be in accordance with **Northstate Carpet Mills Technical Bulletin - Installation Procedures and Requirements, and ASNZS 2455.1:2007**. In direct-stick installations, all seams and cross joins must be sealed with a seam sealing adhesive. In double-bond and carpet gripper installations, all edges to be seamed must be sealed first with an edge sealing adhesive and an appropriate hot-melt adhesive seaming tape must be applied to all seams and cross joins. All unprotected edges must be sealed with an edge sealing adhesive.
- Northstate Carpet Mills manufactures to a high degree of quality however there are certain visual aspects in making of carpet that must be regarded as within manufacturing limits and do not affect the performance of the carpet.
- Pattern carpet with directional designs may be subject to pattern distortion. Exact colour &/or texture pattern match cannot be guaranteed.
- This carpet may impart shift lines across the width, this is not a manufacturing fault and will not detract from the carpets performance.
- Due to dyelot variations, actual material may vary from sample.
- Full details and explanations can be found on our website www.northstatecarpets.com.au
- Supporting our *ECO-focused* initiative, Northstate Carpet Mills where ever possible, use recycled, recyclable and bio-degradeable materials.

NORTHSTATE CARPET MILLS PTY LTD reserves the right to modify this specification to improve the product without prior notice and without prejudice.

E & O E



Rating - Limited Warranties

5 Year Commercial - Commercial Medium Duty (including stairs)
7 Year Residential - Residential Heavy Duty (including stairs)
Abrasive Wear ZipperLock[®] StainFree
Anti-Shock ColourFast
see full warranty text for details



Fire Hazard Properties (B.C.A. Spec C1.10a)

Direct-Stick - Tested to AS/ISO 9239-1
Suitable for ALL building classifications,
except non-sprinklered Class 9a (Patient Care) and
Class 3 (Accommodation for the Aged)
**Verify building classifications with your local building
authority and/or council.**
Consult your Northstate representative for specific details.



ZipperLock[®] Technology

In regular loop pile carpet, one loose yarn can unravel into an
unsightly continuous zipper.
Dual Bonding and Interlocking Tuft Placement means this
Northstate carpet cannot unravel like regular commercial carpet.



Environmentally Friendly

Solution Dyeing is an environmentally friendly dyeing method that
conserves energy and uses 90% less water than conventional
dyeing processes.



Carpet Protection

Scoured & Extracted[™] to remove processing oils,
Anti-microbial present in backing laminate.

This carpet will look and perform better for longer, minimising
re-soiling, enabling ease of spot cleaning and vacuuming, and
ensuring lasting hygienic freshness.



AIRTEX green backing system

AIRTEX green is a new and improved backing system. Spills and
accidents no longer spell disaster. Carpet with AIRTEX green will
not harbour or promote the growth of bacteria, nor will it omit odours.



Anti-Shock, Computer Friendly

This carpet will not generate a static shock exceeding 3.0 kV at
relative humidity of 20% or more and a room temperature of 20° C.