Northstate

Simply better carpet.

ABN 14010558540

BOREALIS

PRODUCT BULLETIN

Series 26L - Nylon

Manufacturer **Country of Manufacture**	Northstate Carpet Mills Australia
Fibre System **Coloration** **Construction** **Pile Weight**	Ultrel™ Nyon 12% pre-consumer recycled content in face fibre Solution Dyed / Space Dyed Interlocking Level Loop Pile 26 oz/sq yd 881.57 g/sq m
Backing System **Primary Backing** **Secondary Backing**	Dual Latex bonding Woven Synthetic AIRTEX green
Carpet Protection	Scoured & Extracted™ to remove processing oils, PermaSeal™ stainblocker and soil release treatment, Anti-microbial present in backing laminate.
Fire Hazard Properties (B.C.A. Spec.C1.10a)	**Direct-Stick** - Tested to AS/ISO 9239-1 Suitable for *ALL* building classifications. **Conventional & Double-Bond with underlay** - Tested to AS/ISO 9239-1 Suitable for *ALL* building classifications, except non-sprinklered Class 9a (Patient Care) and Class 3 (Accommodation for the Aged). ***Verify building classifications with your local building authority and/or council.*** *Consult your Northstate representative for specific details.*
Static Generation **Light Fastness** **Change on Wet Cleaning**	< 3.0kv L6 Gray Scale 5
Approx pattern repeat **Installation Method** **Chair Protectors**	Not Applicable Suitable for direct-stick or cushion installations Mandatory under chairs with castors to preserve appearance retention, and avoid premature wear.
Rating **15 Year Commercial Limited Warranties** *see full warranty text for details*	Commercial Extra Heavy Duty (including stairs) Abrasive Wear ZipperLock® StainFree ColourFast Anti-Shock

- Installation to be in accordance with **Northstate Carpet Mills Technical Bulletin - *Installation Procedures and Requirements,* and ASNZS 2455.1:2007.** In direct-stick installations, all seams and cross joins must be sealed with a seam sealing adhesive. In double-bond and carpet gripper installations, all edges to be seamed must be sealed first with an edge sealing adhesive and an appropriate hot-melt adhesive seaming tape must be applied to all seams and cross joins. All unprotected edges must be sealed with an edge sealing adhesive.
- Northstate Carpet Mills manufactures to a high degree of quality however there are certain visual aspects in making of carpet that must be regarded as within manufacturing limits and do not affect the performance of the carpet.
- Pattern carpet with directional designs may be subject to pattern distortion. Exact colour &/or texture pattern match cannot be guaranteed.
- This carpet may impart shift lines across the width, this is not a manufacturing fault and will not detract from the carpets performance.
- Due to dyelot variations, actual material may vary from sample.
- Full details and explanations can be found on our website www.northstatecarpets.com.au
- Supporting our *ECO-focused* initiative, Northstate Carpet Mills where ever possible, use recycled, recyclable and bio-degradeable materials.

NORTHSTATE CARPET MILLS PTY LTD reserves the right to modify this specification to improve the product without prior notice and without prejudice. Ultrel™ is a registered trademark of Strudex Fibres Limited; used by permission. E & O E

Rating
Commercial Extra Heavy Duty (including stairs)
15 Year Commercial Limited Warranties
Abrasive Wear ZipperLock®
StainFree ColourFast Anti-Shock
see full warranty text for details

Fire Hazard Properties (B.C.A. Spec C1.10a)

Direct-Stick - Tested to AS/ISO 9239-1
Suitable for *ALL* building classifications.
Conventional & Double-Bond with u/lay - Tested to AS/ISO 9239-1
Suitable for *ALL* building classifications,
except non-sprinklered Class 9a (Patient Care) and
Class 3 (Accommodation for the Aged)
Verify building classifications with your local building authority and/or council.
Consult your Northstate representative for specific details.

ZipperLock® Technology

In regular loop pile carpet, one loose yarn can unravel into an unsightly continuous zipper.
Dual Bonding and ***Interlocking Tuft Placement*** means this Northstate carpet cannot unravel like regular commercial carpet.

Environmentally Friendly

Solution Dyeing is an environmentally friendly dyeing method that conserves energy and uses 90% less water than conventional dyeing processes. *Product contains 12% pre-consumer recycled content in face fibre.*

Carpet Protection

- Scoured & Extracted™ to remove processing oils,
- PermaSeal™ stainblocker and soil release treatment,
- Anti-microbial present in backing laminate.

This carpet will look and perform better for longer, minimising re-soiling, enabling ease of spot cleaning and vacuuming, and ensuring lasting hygienic freshness.

AIRTEX green backing system

AIRTEX green is a new and improved backing system. Spills and accidents no longer spell disaster. Carpet with AIRTEX green will not harbour or promote the growth of bacteria nor will it omit odours.

Anti-Shock, Computer Friendly

This carpet will not generate a static shock exceeding 3.0 kV at relative humidity of 20% or more and a room temperature of 20° C.