



Northstate

Simply better carpet.

ABN 14010558540

CHARTERS TOWERS

PRODUCT BULLETIN

Series 34C - Nylon

Fibre System	Nylon
Coloration	100% Solution Dyed
Construction	Level Cut Loop (LCL)
Pile Weight	34 oz/sq yd 1152.82 g/sq m
Backing System	Dual Latex bonding
Primary Backing	Woven Synthetic
Secondary Backing	100% Synthetic
Carpet Protection	Scoured & Extracted™ to remove processing oils PermaSeal™ stainblocker and soil release treatment Anti-microbial present in backing laminate
Fire Hazard Properties (B.C.A. Spec.C1.10a)	Direct-Stick, Conventional & Double-Bond with underlay - Tested to AS/ISO 9239-1 Suitable for ALL building classifications. Verify building classifications with your local building authority and/or council. <i>Consult your Northstate representative for specific details.</i>
Static Generation (AS2834)	< 3.0kv
Light Fastness	L6
Change on Wet Cleaning	Gray Scale 5
Approx pattern repeat	Width 46 x Length 27 cm
Installation Method	Suitable for direct-stick or cushion installations
Chair Protectors	Mandatory under chairs with castors to preserve appearance retention, and avoid premature wear.
Rating 15 Year Commercial Limited Warranties <i>see full warranty text for details</i>	Commercial Extra Heavy Duty (including stairs) Abrasive Wear Anti-Shock StainResist ColourFast

- Installation to be in accordance with **Northstate Carpet Mills Technical Bulletin - Installation Procedures and Requirements, and ASNZS 2455.1:2007**. In direct-stick installations, all seams and cross joins must be sealed with a seam sealing adhesive. In double-bond and carpet gripper installations, all edges to be seamed must be sealed first with an edge sealing adhesive and an appropriate hot-melt adhesive seaming tape must be applied to all seams and cross joins. All unprotected edges must be sealed with an edge sealing adhesive.
 - Northstate Carpet Mills manufactures to a high degree of quality however there are certain visual aspects in making of carpet that must be regarded as within manufacturing limits and do not affect the performance of the carpet.
 - Pattern carpet with directional designs may be subject to pattern distortion. Exact colour &/or texture pattern match cannot be guaranteed.
 - Carpets with linear designs and in particular, carpets constructed with contrasting colours side by side to produce a sisal effect may be subject to random colour banding across the carpet.
 - Due to dyelot variations, actual material may vary from sample.
 - Full details and explanations can be found on our website www.northstatecarpets.com.au
 - Supporting our *ECO-focused* initiative, Northstate Carpet Mills where ever possible, use recycled, recyclable and bio-degradable materials.
- NORTHSTATE CARPET MILLS PTY LTD reserves the right to modify this specification to improve the product without prior notice and without prejudice.**
- E & O E**



Rating

Commercial Heavy Duty (including stairs)
15 Year Commercial Limited Warranties
Abrasive Wear Anti-Shock
StainResist ColourFast
see full warranty text for details



Fire Hazard Properties (B.C.A. Spec C1.10a)

Direct-Stick, Conventional & Double-Bond with underlay -
Tested to AS/ISO 9239-1
Suitable for ALL building classifications.
Verify building classifications with your local building authority and/or council.
Consult your Northstate representative for specific details.



Shading

Cut pile carpets sometimes develop irregular areas of light and dark. This is caused by the pile changing its original lay thereby changing the way the light is reflected. This is not a manufacturing fault and has no detrimental effect on the carpets performance. For further information please refer to the Carpet Institute of Australia's booklet '*Permanent Pile Reversal Shading*'.



Environmentally Friendly

Solution Dyeing is an environmentally friendly dyeing method that conserves energy and uses 90% less water than conventional dyeing processes.



Carpet Protection

- Scoured & Extracted™ to remove processing oils,
- PermaSeal™ stainblocker and soil release treatment,
- Anti-microbial present in backing laminate.

This carpet will look and perform better for longer, minimising re-soiling, enabling ease of spot cleaning and vacuuming, and ensuring lasting hygienic freshness.



Anti-Shock, Computer Friendly

This carpet will not generate a static shock exceeding 3.0 kV at relative humidity of 20% or more and a room temperature of 20° C.